

# MR-96A

## Microplate Reader

- Touch-screen, 7.8" large color LCD display
- Opaque lid to prevent stray light
- Built-in thermal recorder, optional external printer
- Non-volatile memory stores up to 20,000 results
- Multiple Curve-fitting options
- Variable time and speed shaking modes
- Fully automatic bi-chromatic optical system
- Extensive report with patient information
- Long life lamp with lamp saver feature
- Powerful data management software(optional)





**mindray**  
healthcare within reach

# MR-96A

## Microplate Reader

### Technical Specifications

Detection method	Absorbance
Microplate types	96/48-well plate
Reading speed	5 sec single wavelength, 12 sec double wavelength
Wavelength range	400~700nm
Measurement system	8-channel optical system
Light source	Halogen-tungsten
Reading range	0.001~3.500 Abs
Measurement range	0.001~2.500 Abs
Photometric accuracy	0~0.2 A 0.001 Abs
Wavelength accuracy	±2nm
Repeatability	< 1%
Stability	< 0.005 Abs / 10 min
Linearity	0~1.5 A < 1.0%
Filters	405nm, 450nm, 492nm, 630nm
Connection port	1 x RS232, 2 x USB
Shaking	variable speed and time shaking modes
Input	Touch screen
Display	Large color LCD display
Size	437mm x 332mm x174mm
Weight	8.5 Kg



Data Management Software

DISTRIBUTOR:



MINDRAY is a trademark of Shenzhen Mindray Bio-Medical Electronics Co.,Ltd. Specifications subject to changes without prior notice.  
© 2010 Shenzhen Mindray Bio-Medical Electronics Co., Ltd. All rights reserved.  
PIN: ENG-MR96A-210285x2-20100203

**mindray**

Mindray is listed on the NYSE under the symbol "MR"  
Mindray Building, Keji 12th Road South, High-tech Industrial Park,  
Nanshan, Shenzhen 518057, P.R. China  
Tel: +86 755 26582888 Fax: +86 755 26582680  
E-mail: intl-market@mindray.com Website: www.mindray.com